


### SR-EOH10S-220

SR-EOH15S-220



S MARE	
/	

1 inv 10kW 2 Bat 10.24kWh

1 inv 10kW 3 Bat 15.36kWh

Inverter Module	SR-EOH10S-220	Can Be Set
Output		
Rated Output Power	10,000W	
Max. Peak Power	20,000VA	
Load Capacity of Motor	6HP	
Wave Form	Pure Sine Wave	
Rated Output Voltage	230Vac (single phase)	$\checkmark$
Solar Input		
Solar Charge Type	MPPT	
Max. Solar Array Power	5,500W+5,500W	
Max. Solar Open Circuit Voltage	500Vdc	
Grid / Generator Input		
Input Voltage Range	90~270Vac	
Bypass Overload Current	63A	
Battery Charging		
Max. Solar Charging Current	200A	$\checkmark$
Max. Grid/Generator Charging Current	120A	$\checkmark$
General		
Dimension	655*353*185mm (2.14*1.15*0.6ft)	

Battery Module	SR-EOH05B	Can Be Set
Battery Power	5.12kWh	
Rated Voltage	51.2V	
Rated Capacity	100Ah	
Battery Type	LFP	
Crycling Lifespan	6000 (80%DOD,0.5C,25°C)	
Max. Parallel Capacity	9 units (up to 46.08kWh)	$\checkmark$
Dimension	655*353*185mm (2.14*1.15*0.6ft)	
Standard	UN38.3,MSDS,IEC62619,UL1973,IEC61000-6:2019,RoHS	

- 🕄 Easy to upscale

## local User friendly

• The system offers various charging methods, including

# 🕞 Safety

- High quality lithium iron phosphate cells
- Proven Li–ion battery management solutions

# Easy to install

## **Ø** Intelligence

- Users can set the charging and discharging time of the

## **•** Designed for families




Up to 9 batteries are connected in parallel to obtain the required energy storage and power output

## SR-EOH20S-220

SR-EOH25S-220



1 inv 10kW 4 Bat 20.48kWh



### 1 inv 10kW 5 Bat 25.6kWh