



All- in- one Solar Storage System

Plug and play, saving time, effort and installation costs.

5kW

- □ The minimum width is only 13cm, saving space in your home.
- Supports wall-mounted and floor- standing installation.
- □ Support Wifi, real-time data can be viewed through APP.
- □ Integrated circuit breaker improves system safety.
- Equipped with manual bypass switch to facilitate manual switching of power supply mode.
- □ With hybrid load function, solar energy can be utilized to
- can be expanded to 20.48kWh.

ABOUT SRNE -

- □ SRNE 15 years in PV industry, committed to independent R&D and production.
- $\hfill\Box$ Holds over 200 patents in energy storage, with unique industryleading technologies.
- ☐ Chooses top-quality international components to deliver highvalue products to customers.
- □ Upholds values of customer priority, proactivity, responsibility, and innovative breakthroughs.

SRNE Solar Co,.ltd www.srnesolar.com





All-IN-ONE MODEL	SR-EOT05S-110
INVERTER OUTPUT	
Rated Output Power	5,000W
Max.Peak Power	10,000VA
Load Capacity of Motor	4HP
Rated Output Voltage	120Vac
BATTERY	
Battery Type	LFP
Battery Energy	5.12kWh
Battery Capacity	100Ah
Battery Rated Voltage	51.2V
Battery Working Voltage Range	44.8~57.6V
Standard Charge current	50A
Max. Charge Current	100A
Cycling Lifespan	6000 (80%DOD,0.5C,25°C)
PV CHARGE	
Max. Output Power	5,500W
Max. input Current	22A
Max. MPPT Charging Current	100A
Max. PV Open Circuit Voltage	500Vdc
MPPT Voltage Range	120-450Vdc
AC CHARGE	
Max. AC Charge Power	2,100W
Max. AC Charging Current	40A
Rated Input Voltage	110/120Vac
Input Voltage Range	90~140Vac
GRID/GENERATOR INPUT	
Input Voltage Range	90∼140Vac
Bypass Overload Current	63A
EFFICIENCY	
MPPT Tracking Efficiency	99.9%
GENERAL	
Protection Degree	IP20, Indoor Only
Dimensions	972*555*130mm
Weight	64kg (141.1lb)
CERTIFICATION	, , , , , , , , , , , , , , , , , , ,
Safety	MSDS,UN38.3,IEC61000-6:2019,NRS097
RoHS	Yes
BATTERY MODEL	SR-EOV05B

BATTERY MODEL	SR-EOV05B
MAIN INFO	
Battery Power	5.12kWh
Rated Voltage	51.2V
Rated Capacity	100Ah
Standard charge current	50A
Max. charge current	100A
Battery Type	LFP
Cycling Lifespan	6000 (80%DOD,0.5C,25°C)
Max. Parallel Capacity	3 units (up to 15.36kWh)
GENERAL	
Gross Weight	45kg (99.21lb)
Dimension	600*555*130mm(1.97*1.82*0.42ft)
Protection Degree	IP20
STANDARD	
Transportation	UN38.3
Safety	CE-GPSD,IEC62109,EMC