

MAIN

MODEL	DB-12
Power consumption	≤40mA
Communication function	Bluetooth、RS485、CAN(RV-C)
System voltage	12V/24V
INPUT1 maximum input current	120A
INPUT2 maximum input current	30A
Input voltage range	9~32V
Ambient temperature	-35°C~+65°C
Cooling method	Natural cooling
Product weight	1.1Kg
Product size	263.6*119.8*48.6mm
Product function	Battery overdischarge protection; battery overvoltage protection; load overcurrent protection.

FUNCTION

DB12 is a multi-way DC load switch control box designed specifically for RVs. When paired with the RM12 touch control panel or mobile, it can achieve the switching of 12 DC loads and 1 inverter remote switch in RVs.

DB12 DC distribution box has 3 load output interfaces of 30A, 3 of 20A, and 6 of 10A, which is used to control the power supply of RV DC loads, such as refrigerators, water pumps, TVs, lights, etc

CONNECTION SKETCH



FEATURE -

- □ Supports 12V/24V battery systems, Total current 100A
- □ With battery overvoltage, over-discharge, and load overcurrent protection functions.
- □ Supports various battery types including sealed, gel, open, lithium-ion, and customizable options.
- □ The battery's overvoltage and over-discharge voltage can be set.
- □ Built-in Bluetooth communication, enabling real-time monitoring, parameter settings, and load switching operations through a mobile APP.
- □ Supports RS485, CAN (RV-C protocol) communication.
- □ Supports 12 DC load outputs, each output is equipped with a plug-in fuse.

ABOUT SRNE -

- □ SRNE 15 years in PV industry, committed to independent R&D and production.
- □ Holds over 200 patents in energy storage, with unique industryleading technologies.
- □ Chooses top-quality international components to deliver highvalue products to customers.
- □ Upholds values of customer priority, proactivity, responsibility, and innovative breakthroughs.

SRNF Solar Co., ltd. www.srnesolar.com

