



SR- Ket60B/70B/80B/90B SR- Ket100B/110B/120B/130B 63~136.4kWh Lithium Battery Energy Storage

PRODUCT FEATURE

Tuya cloud platform

Equipped with WIFI and Bluetooth communication, it supports Tuya cloud platform and can view battery information remotely.

Triple protection

Positive Relay + Negative Relay + Breaker, Adopting redundant design to ensure control safety.

Higher safe performance and longer cycle life

Cathode material is made from LiFePO₄ with safety performance and long cycle life.

Flexible Installation

Quick installation standard of 19-inch embedded designed module is comfortable for installation and maintenance.

Intelligent BMS

It has protection functions including over-discharge, over-charge, over-current and over-high or low temperature. The system can automatically manage charge and discharge state and balance current and voltage of each cell.

Flexible configuration

Multiple battery modules can be in parallel for expanding capacity and power.



Battery System Module	SR-Ket60B	SR-Ket70B	SR-Ket80B	SR-Ket90B
Battery Module Qty in series	6	7	8	9
System Nominal Voltage (V)	307.2	358.4	409.6	460.8
System Operating Min.Voltage (V)	268.8	313.6	358.4	403.2
System Operating Max.Voltage (V)	345.6	403.2	460.8	518.4
System Energy (kWh)	63	73.5	84	94.5
System Usable Energy (kWh)	59.8	69.8	79.8	89.7
Recommend Charge/Discharge Current (A)	100/100			
Max Charge/Discharge Current (A)	150/200			
Peak Discharge (3S,25°C) (A)	200/220			
Installation Location	Rack Mounting			
Recommend Depth of Discharge	≤95%			
Cycle Life	6000 (25°C,0.5C/0.5C,EOL70%)			
Display Type	LED+Touch LCD			
Triple Protection	Positive Relay + Negative Relay + Breaker			
Number of Main CircuitRelays	3			
Heat Dissipation	Fan cooling			
Certification	UN38.3/CE/CE-EMC			
Working Temperature (°C)	Charge:0~55°C/Discharge:-20~55°C			
Storage Temperature (°C)	0~35°C			
Communicaton Port	RS485/CAN/WiFi			
Humidity (RH)	5%~80%			
Altitude (m)	≤3000			
IP Rating of Enclosure	IP20			
Noise (dB)	< 50			
Dimensions (WxDxH,mm)	840*590*2095	840*1190*2095		
Weight Approximate (kg)	687.5	779.5	871.5	963.5
Cover An Area (m*m)	0.84*0.59	0.84*1.19		



Battery System Module	SR-Ket100B	SR-Ket110B	SR-Ket120B	SR-Ket130B
Battery Module Qty in series	10	11	12	13
System Nominal Voltage (V)	512	563.2	614.4	665.6
System Operating Min.Voltage (V)	448	492.8	537.6	582.4
System Operating Max.Voltage (V)	576	633.6	691.2	748.8
System Energy (kWh)	105	115.5	126	136.4
System Usable Energy (kWh)	99.7	109.7	119.7	129.7
Recommend Charge/Discharge Current (A)	100/100			
Max Charge/Discharge Current (A)	150/200			
Peak Discharge (3S,25°C) (A)	200/220			
Installation Location	Rack Mounting			
Recommend Depth of Discharge	≤95%			
Cycle Life	6000 (25°C,0.5C/0.5C,EOL70%)			
Display Type	LED+Touch LCD			
Triple Protection	Positive Relay + Negative Relay + Breaker			
Number of Main CircuitRelays	3			
Heat Dissipation	Fan Cooling			
Certification	UN38.3/CE/CE-EMC			
Working Temperature (°C)	Charge:0~55°C/Discharge:-20~55°C			
Storage Temperature (°C)	0~35°C			
Communicaton Port	RS485/CAN/WiFi			
Humidity (RH)	5%~80%			
Altitude (m)	≤3000			
IP Rating of Enclosure	IP20			
Noise (dB)	< 50			
Dimensions (WxDxH,mm)	840*1190*2095			
Weight Approximate (kg)	1055.5	1147.5	1239.5	1331.5
Cover An Area (m*m)	0.84*1.19			





PDU Module	SR-PDU200B
Rated Voltage (V)	850
Rated Current (A)	200
Operating Voltage (V)	100~850
CAN Communication	2
Relay Control	3
LCD Screen (inch)	4.3
Breaker (A)	300
Relay (A)	250
Fuse (A)	315
Precharge Relay (A)	50
Precharge Resistance (W/Ω)	200/100
External DC input port (V)	24
Dimensions (WxDxH,mm)	608*504*253
Weight Approximate (kg)	17.5



Battery Pack Module	SR-HOF10B
Battery Type	LiFePO4
Battery Energy (kWh)	10.49
Rated Voltage (V)	51.2
Rated Capacity (Ah)	205
Recommend Charge/Discharge Current (A)	100/100
Max Charge/Discharge Current (A)	150/200
Peak Discharge (3S,25°C) (A)	200/220
Installation Location	Rack Mounting
Recommend Depth of Discharge	≤95%
Cycle Life	6000 (25°C,0.5C/0.5C,EOL70%)
Heat Dissipation	Fan Cooling
Working Temperature (°C)	Charge:0~55°C/Discharge:-20~55°C
Storage Temperature (°C)	0~35°C
IP Rating of Enclosure	IP20
Dimensions (WxDxH,mm)	608*504*253
Weight Approximate (kg)	90



Single cluster standard rack	SR-Rack-7B
Single cluster standard rack size (WxDxH,mm)	840*590*2095
Single cluster standard rack weight (kg)	118
Single cluster Max. battery number(units)	6
Two clusters Max. battery number(units)	13